

FORD TRUCKS 1848T LOW LINER EURO6





| Basic Features | | | | |
|-------------------------|---|--|--|--|
| Vehicle Type | Tractor-Lowliner | | | |
| Axle | 4x2 | | | |
| Emission | Euro 6 | | | |
| Cabin Type | Extra High Roof Sleeper Cab | | | |
| Wheelbase (mm) | 3600 | | | |
| Engine | | | | |
| Type | Ecotorq 12,7 lt | | | |
| Displacement (cc) | 12740 | | | |
| Diameter x Stroke | 130 mm x 160 mm | | | |
| Power | 480 PS (353 kW) / 1800 rpm | | | |
| Torque | 2500 Nm / 1000 - 1200 rpm | | | |
| Compression Ratio | 17 +/- 0,5 : 1 | | | |
| Oil Filling Volume | 50 L | | | |
| Coolant Volume | 37 L (57 L with Intarder) | | | |
| Transmission | | | | |
| Clutch | 430mm Single Disc | | | |
| Automated Transmission | ZF 12 TX 2620 (16,688-1) | | | |
| Steering | | | | |
| | Power Assisted Single Circuit | | | |
| Chassis | | | | |
| Chassis Thickness (mm) | 10 mm | | | |
| Chassis Strength (MPa) | 500 MPa | | | |
| Suspension (Front/Rear) | 90 mm Parabolic Leaf Springs / Air Suspension | | | |
| Axle | Single Reduction | | | |

| Chassis | | | | | |
|---|---|--|--|--|--|
| Chassis Thickness (mm) | 10 mm | | | | |
| Chassis Strength (MPa) | 500 MPa | | | | |
| Suspension (Front/Rear) | 90 mm Parabolic Leaf Springs / Air Suspension | | | | |
| Axle | Single Reduction | | | | |
| Axle Ratio | 2,47 | | | | |
| Tyres (Front/Rear) | 315/60 R22.5 / 295/60 R22.5 | | | | |
| Wheel Rim | 22,5 x 9 Steel | | | | |
| Braking System | | | | | |
| Brakes (Front/Rear) (Ø.mm x mm. Length) | 430 x 45 - Disc Brakes | | | | |
| Braking System | Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater | | | | |
| Engine Brake Power | max. 340 kW (Engine Level) | | | | |
| Intarder Power | max. 600 kW / continuous 160 kW | | | | |

| Intarder Power | max. 600 kW / continuous 160 kW |
|----------------------------|---------------------------------|
| Electrical System | |
| Battery | 24V, 2 x 12V 225 Ah |
| Alternator / Starter Motor | 130 A / 6,5 kW |
| Tanks | |
| Fuel Tank | 510 L + 410 L Aluminium |
| SCD Taple | 551 |





| Dimensions (mm) | | | | |
|---|---|---------|-------|--|
| 5 th Wheel Height | | 980 | | |
| Front Overhang | | 1500 | | |
| Wheelbase | | 3600 | | |
| Overall Length | | 6150 | | |
| Overall Cab Length | | 2305 | | |
| Total Height | 3802 (Extra High Roof); 2956 (Low Roof) | | | |
| Overall Vehicle Width (Excluding Mirrors) | | 2540 | | |
| Chassis Width | | 866 | | |
| Rear Overhang | | 1050 | | |
| Chassis Height-Front | | 225 | | |
| Chassis Height-Rear | | 209 | | |
| Ground Clearance-Front | | 292 | | |
| Ground Clearance-Rear | | 246 | | |
| Turning Radius | | 7500 | | |
| Weights (kg) | 1. Axle | 2. Axle | Total | |
| Technically Permissible Weights | 7100 | 12300 | 18000 | |
| Kerb Weight | 5545 | 2265 | 7732 | |
| Payload | 1555 | 10035 | 10268 | |
| GVM (Legal) | 7100 | 11500 | 18000 | |

STANDARD EQUIPMENT

- Air Conditioner
- Radio/CD Player
- Extra High Roof Cab with Double Bed
- Dry Type Cab Heater
- Air Suspended Cab
- Power Cab Tilting
- Cruise Control
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Electrically Operated Sunroof
- Front and Rear Vehicle Antiroll Bar
- Disc Brakes
- Automated Transmission (with Different Usage Modes)
- Electronic Brake System (EBS) and Anti-Lock Brake System (ABS)
- Active Emergency Brake System (AEBS)
- Electronic Brake Force Control
- Brake Assistant
- Electronic Stability Program (ESP)
- Brake Lining Wear Sensor
- Lane Departure Warning System (LDWS)
- Auto Light Sensor
- Rain Sensor
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
- Switchable Air Compressor for Improved Fuel Economy
- Variable Steering Pump for Improved Fuel Economy
- Hill Launch Assist
- Coupling Force Control
- Front Fog Lamps
- Spoiler *
- Axle Load Indicator

OPTIONAL EQUIPMENT

- Intarder
- ADR Pack
- Low Roof Sleeper Cab with Single Bed
- Wet Type Cabin Heater
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry & Wet Type Cab Heater
- Engine Driven PTO & Interior Control Unit
- Transmission PTO & Interior Control Unit



This leaflet includes products designed for Ford vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications.